



KURTMAN

GAI-R Female connector
Female BSPB thread (ISO 1179-1) 24° cone end

DRE-R DİŞİ REKOR

Gövde sipariş kodu



Order code without nut and cutting ring

XDRE....(X261...)

Komple sipariş kodu

Order code with nut and cutting ring

DRE....(261...)



Series	Tube ØD1 Boru Çapı	T1	D3	L1	L2	L3	L4	S1	S2	Weight g/1 piece	ITEM CODE	ITEM NAME	PN (bar)
											PARÇA KODU	PARÇA ADI	
L NB	6	G 1/8A	4	26.0	19.0	12.0	34	14	14	18	261210602	DRE6NBR02	315
	6	G 1/4A	4	31.0	24.0	17.0	39	19	14	40	261210604	DRE6NBR04	315
	8	G 1/4A	6	31.0	24.0	17.0	39	19	17	56	261210804	DRE8NBR04	315
	8	G 3/8A	6	32.0	25.0	17.0	40	24	17	64	261210806	DRE8NBR06	315
	8	G 1/2A	6	36.0	29.0	20.0	44	27	17	82	261210808	DRE8NBR08	315
	10	G 1/4A	8	32.0	25.0	17.0	40	19	19	40	261211004	DRE10NBR04	315
	10	G 3/8A	8	33.0	26.0	17.0	41	24	19	65	261211006	DRE10NBR06	315
	10	G 1/2A	8	37.0	30.0	20.0	45	27	19	84	261211008	DRE10NBR08	315
	12	G 3/8A	10	33.0	26.0	17.0	41	24	22	63	261211206	DRE12NBR06	315
	12	G 1/2A	10	37.0	30.0	20.0	45	27	22	83	261211208	DRE12NBR08	315
	15	G 1/2A	12	38.0	31.0	20.0	46	27	27	89	261211508	DRE15NBR08	315
	18	G 1/2A	15	38.0	30.5	20.0	47	27	32	91	261211808	DRE18NBR08	315
	18	G 3/8A	15	34.0	26.5	17.0	43	27	32	95	261211806	DRE18NBR06	315
	22	G 3/4A	19	43.0	35.5	22.0	52	36	36	177	261212212	DRE22NBR12	160
	28	G 1A	24	45.5	38.0	24.5	55	41	41	212	261212816	DRE28NBR16	160
	35	G 1 1/4A	30	51.5	41.0	26.5	63	55	50	464	261213520	DRE35NBR20	160
S YB	42	G 1 1/2A	36	53.5	42.5	28.5	65	60	60	541	261214224	DRE42NBR24	160
	6	G 1/4A	4	33.0	26.0	17.0	41	19	17	44	261310604	DRE6YBR04	630
	8	G 1/4A	5	33.0	26.0	17.0	41	19	19	46	261310804	DRE8YBR04	630
	10	G 3/8A	7	34.0	26.5	17.0	43	24	22	68	261311006	DRE10YBR06	630
	12	G 3/8A	8	34.0	26.5	17.0	43	24	24	78	261311206	DRE12YBR06	630
	12	G 1/2A	8	38.0	30.5	20.0	47	30	24	121	261311208	DRE12YBR08	630
	14	G 1/2A	10	40.0	32.0	20.0	50	30	27	124	261311408	DRE14YBR08	630
	16	G 1/2A	12	40.0	31.5	20.0	50	30	30	126	261311608	DRE16YBR08	400
	20	G 3/4A	16	45.0	34.5	22.0	56	36	36	190	261312012	DRE20YBR12	400
	25	G 1A	20	49.5	37.5	24.5	62	41	46	244	261312516	DRE25YBR16	400
	30	G 1 1/4A	25	55.5	42.0	26.5	69	55	50	509	261313020	DRE30YBR20	400
	38	G 1 1/2A	32	59.5	43.5	28.5	74	60	60	623	261313824	DRE38YBR24	315

L= light series NB= Normal basınç

S= heavy series YB= Yüksek basınç

PN (bar) = PN (MPa)
10

Çinko Kaplama / Zinc plated=Cr(VI)-free